



AK Series Under-the-Press Granulator

Model	Cutting Circle	Throughput	Motor HP	Auger Feed Opening*	Ship Weight
AK68	6" (152mm)	175 lbs/hr (79kg)	3-5 HP (2.2-3.7kW)	7" x 14" (178 x 356mm)	650 lbs. (295kg)
AK812	8" (203mm)	250 lbs/hr (113kg)	5 HP (3.73kW), 7.5 HP (5.59kW)	10" x 24" (254 x 610mm)	1300 lbs. (590kg)
AK1216	12" (305mm)	450 lbs/hr (204kg)	10 HP (7.46kW), 15 HP (11.18kW)	15" x 27" (381 x 686mm)	2400 lbs. (1089kg)

*Auger-Fed granulators must be guarded to prohibit inadvertent access to the moving auger. For outside of the press applications, the auger feed chutes dimensioned above provide minimum operator-safe distances from point of feed. Customer furnished chutes must adhere to these minimum dimensions. For interface to conveyors, separators, or other outside of the press equipment, consult factory for specific recommendations.

WG Series Under-the-Press Granulator

Model	Cutting Circle	Throughput	Motor HP	Throat Size	Ship Weight
WG36	7.9" (200mm)	800-1200 (363-545kg)	7.5-20 HP (5.6-14.9kW)	8" x 36" (203 x 914mm)	2600 lbs (1181kg)
WG56	7.9" (200mm)	1000-1500 lbs/hr (454-681kg)		8" x 56" (203 x 1422mm)	2900 lbs (1305kg)

WG1200 Series Under-the-Press Granulator

Model	Cutting Circle	Throughput	Motor HP	Feed Height	Ship Weight
WG1244	12" (305mm)	1600 lbs/hr (725kg)	20 HP (14.9kW)	30" (762mm)	4000 lbs (1814kg)
WG1256		2000 lbs/hr (907kg)	30 HP (22.3kW)		5300 lbs (2404kg)
WG1274		2800 lbs/hr (1270kg)	40 HP (29.8kW)		8000 lbs (3629kg)